

1300-system (C2)

PVX1300C2- US

- ✓ open C-format crimp head
- ✓ DUAL crimp technology
- ✓ ergonomic design
- ✓ swivel fork
- ✓ crimp force control using pressure monitoring
- ✓ display with information about the tool and service intervals
- ✓ crimp monitoring with warning lamp (LED)



Battery powered crimp tool for contact crimping
Cu-terminals, type KRF/KSF 10-300 mm², C-sleeves
6/6-120/120 mm².



Item number: **5204-011400**

EAN: **7393487061231**

Delivery box: **Plastic case**

Working temperature, Min (°C): **-20**

Working temperature, Max (°C): **40**

Crimp geometries: **Dual, Hexagonal, Oval**

Pressure monitoring via display: **Yes**

Charge time (min): **15**

AWG/MCM Cu: **8 AWG - 700 MCM**

mm² Cu: **10-400**

mm² KR/KS, KRF/KSF: **10-400**

mm² KRT/KST: **10-400**

mm² KRD/KSD: **10-400**

Crimp range Cu-terminals min (mm²): **10**

Crimp range Cu-terminals max (mm²): **400**

Crimp range C-connectors min (mm²): **6**

Crimp range C-connectors max (mm²): **120**

Matching items

Product	ItemMM2KRdKSorKRFdKSF	ItemMM2KRTdKST	ItemMM2KRDdKSD
13CBC13	—	—	—
13CBC15	—	—	—

EIPRESS