

Aluminium-copper through connectors 16 - 500  
mm<sup>2</sup>

# AKS240-70

- ✓ Connector from Al conductor to Cu conductor.
- ✓ Stranded/solid Al conductors, stranded/multi-stranded Cu conductors.
- ✓ For multi-stranded Cu conductors, contact crimping using the Dual system is recommended.
- ✓ Two crimps are required for Al, normally one for Cu.

AlCu through connector, from Al conductor to Cu conductor. For stranded Al cable 240 mm<sup>2</sup> to stranded/multi-stranded Cu cable 70 mm<sup>2</sup>. When crimping the Cu section, place the dies between the mark on the sleeve and the edge of the Cu section. Used with Elpress certified systems V1300, V250.



Item number: **7333-405400**

EAN: **7393487010208**

s1 (mm): **25**

d (mm): **19.8**

D (mm): **32**

L (mm): **93.5**

d1 (mm): **13**

D1 (mm): **17**

s (mm) - strip length: **61**

AWG/MCM Stranded Al: **450 MCM**

AWG/MCM Cu: **2/0 AWG**

mm<sup>2</sup> Stranded Al: **240**

mm<sup>2</sup> Cu: **70**

Screen conductor (mm<sup>2</sup>): **72-88**

