

KRF70-8- 90GR

- ✓ Material: Cu 99.95%, tin plated Cu/Sn.
- ✓ Inspection hole.
- ✓ For stranded (class 2) and multi-stranded (class 5) Cu conductors, for multi-stranded Cu conductors contact crimping using the Dual system is recommended.
- ✓ UL-approved, DNV approved.

Example of marking KRF: 17 (neck) Elpress logo 70 10F (palm)

17 = Die No. 70 = mm² 10 = palm hole for M10 F = type KRF for stranded and flexible conductors.

Angled tube terminal 90° for multi-stranded (class 5) and stranded (class 2) Cu conductors (acc. to IEC 60228), 70 mm², with an M8 hole in the palm. Used with Elpress certified systems V600, V1300, V250.



UK
CA

Item number: **7301-116400**

EAN: **7393487016453**

A (mm): **31.5**

W (mm): **24**

N (mm): **8.5**

N1 (mm): **17.5**

P (mm): **26**

d (mm): **13**

D (mm): **17**

t (mm) - palm thickness: **3.9**

s (mm) - strip length: **22**

Screw: **M8**

Angle (°): **90**

Inspection hole: **Yes**

AWG/MCM Cu: **2/0 AWG**

mm² Cu: **70**

