

KRFS tube terminals 50 - 400 mm² with narrow palm

KRFS300A- 10

- ✓ Material: Cu 99.95%, tin plated Cu/Sn.
- ✓ Inspection hole
- ✓ For stranded (class 2) and multi-stranded (class 5) Cu conductors, for multi-stranded Cu conductors contact crimping using the Dual system is recommended.
- ✓ Easy to install via cable gland, allows for pre-installation.
- ✓ The width of the palm is less than or as wide as the neck.

Example of marking KRFS: 17 (neck) Elpress logotype 70 10F (palm)

17 = Die no. 70 = mm² 10 = palm hole for M10 F = type KRF for stranded and flexible conductors.
Tube terminal with narrow palm for multi-stranded (class 5) and stranded (class 2) Cu conductors (acc. to IEC 60228), 300 mm², with an M10 hole in the palm. Used with Elpress certified systems V1300 or V250.



Item number: **7301-292900**

EAN: **7393487062160**

W (mm): **31**
N (mm): **15**
N1 (mm): **19**
P (mm): **34**
f (mm): **1.25**
d (mm): **24.5**
D (mm): **31,5**
L1 (mm): **79**
L (mm): **94**
t (mm) - palm thickness: **8.6**
s (mm) - strip length: **40**

Screw: **M10**

Inspection hole: **Yes**

AWG/MCM Cu: **550 MCM**
mm² Cu: **300**

