

1300-system (H)

DV1300

- ✓ crimp head with patented DUAL technology that gives optimised hexagonal crimping + a certain amount of indented crimping in two integrated steps
- ✓ working pressure 63 MPa (630 bar)
- ✓ crimp force 130 kN (13 tonnes)
- ✓ light and versatile steel crimp head

Crimp head with patented DUAL technology for contact crimping Cu terminals, type KRF/KSF 10-300 mm². Used in conjunction with Elpress foot pump P4000 or battery and mains powered pump PS710.



Item number: **5208-133500**

EAN: **7393487026285**

Working temperature, Min (°C): **-20**

Working temperature, Max (°C): **40**

Crimp geometries: **Punch, Dual, Hexagonal, Oval**

Working pressure (MPa): **63**

Quick connector: **Yes**

AWG/MCM Stranded Al: **6 AWG - 700 MCM**

AWG/MCM Solid Al: **6 AWG - 450 MCM**

AWG/MCM Cu: **8 AWG - 700 MCM**

mm² Stranded Al: **16-400**

mm² Solid Al: **16-240**

mm² Cu: **10-400**

Crimp range Cu-terminals min (mm²): **10**

Crimp range Cu-terminals max (mm²): **400**

Crimp range C-connectors min (mm²): **25**

Crimp range C-connectors max (mm²): **240**

Crimp range Al-terminals min (mm²): **16**

Crimp range Al-terminals max (mm²): **400**

Matching items

Product	mm ² KR/KS, KRF/KSF	mm ² KRT/KST	mm ² KR D/KSD
13B11	25	—	35
13B11L	25	—	—



ELPRESS

Product	mm² KR/KS, KRF/KSF	mm² KRT/KST	mm² KRD/KSD
13B12	—	35	50
13B14	—	50	70
13B16	—	70	95
13B19	—	120	120
13BC8-9	—	—	—
13DB8	10	—	—
13DB9	16	—	—
13DB11	25	—	—
13DB13	35	—	—
13DB14,5	50	—	—
13DB17	70	—	—
13DB20	95	—	—
13DB22	120	—	—
13DB25	150	—	—
13DB27	185	—	—
13DB30	240	—	—
13DB32	300	—	—
13P13M2	—	—	—