

1300-system (H)

V1300

- ✓ working pressure 63 MPa (630 bar)
- ✓ crimp force 130 kN (13 tonnes)
- ✓ light and versatile steel crimp head

Crimp head for contact crimping Cu terminals, type KRF/KSF 10-400 mm², Al terminals 16-400 mm² (-240 solid), C sleeves 6/6-120/120 mm². Used in conjunction with foot pump P4000 or battery and mains powered pump PS710.



Item number: **5208-132500**

EAN: **7393487000520**

Crimp geometries: **Punch, Hexagonal, Oval**

Safety device: **Protective cover**

Working pressure (MPa): **63**

Quick connector: **Yes**

AWG/MCM Stranded Al: **6 AWG - 700 MCM**

AWG/MCM Solid Al: **6 AWG - 450 MCM**

AWG/MCM Cu: **8 AWG - 700 MCM**

mm² Stranded Al: **16-400**

mm² Solid Al: **16-240**

mm² Cu: **10-400**

Crimp range Cu-terminals min (mm²): **10**

Crimp range Cu-terminals max (mm²): **400**

Crimp range C-connectors min (mm²): **6**

Crimp range C-connectors max (mm²): **120**

Crimp range Al-terminals min (mm²): **16**

Crimp range Al-terminals max (mm²): **400**



Matching items

Product	mm ² KR/KS, KRF/KSF	mm ² KRT/KST	mm ² KRD/KSD
13B11L	25	—	—

ELPRESS

Product	mm² KR/KS, KRF/KSF	mm² KRT/KST	mm² KRD/KSD
13B12	—	35	50
13B13	35	—	—
13B14	—	50	70
13B14,5LS	—	—	—
13B16	—	70	95
13B19	—	120	120
13B20	95	—	—
13B22	120	150	150
13B25	150	—	185
13B25DIN	—	—	—
13B26	—	240	—
13B27	185	—	240
13B28DIN	—	—	—
13B30	240	300	300
13B32	300	400	400
13B38	400	—	—
13BC8-9	—	—	—
13BC13	—	—	—
13BC15	—	—	—
13P13M2	—	—	—
B6DIN	—	—	—
B6FE	—	—	—
B7	—	10	—
B8	10	—	16
B8,5	—	16	—
B8DIN	—	—	—
B8FE	—	—	—
B9	16	—	25

Product	mm ² KR/KS, KRF/KSF	mm ² KRT/KST	mm ² KRД/KSD
B10	—	25	—
B10DIN	—	—	—
B11	25	—	35
B12	—	35	50
B12DIN	—	—	—
B13	35	—	—
B14	—	50	70
B14,5	50	—	—
B14DIN	—	—	—
B16	—	70	95
B16DIN	—	—	—
B16NP	—	—	—
B17	70	—	—
B18	—	95	—
B18DIN	—	—	—
B19	—	120	120
B20	95	—	—
B20DIN	—	—	—
B20NP	—	—	—
B22	120	150	150
B22DIN	—	—	—
B24	—	185	—
B25	150	—	185
BC5	—	—	—
BC6	—	—	—
BC8-9	—	—	—