

250-system (25 t)

DV250

- ✓ crimp head with patented DUAL technology that gives optimised hexagonal crimping + a certain amount of indented crimping in two integrated steps
- ✓ fitted with safety device in the form of a protective cover
- ✓ working pressure 63 MPa (630 bar)
- ✓ crimp force 250 kN (25 tonnes)
- ✓ light and versatile steel crimp head

Crimp head for contact crimping Cu terminals, type KRF/KSF 120-400 mm². Used in conjunction with Elpress foot pump P4000 or battery and mains powered pump PS710.



Item number: **5208-250200**
EAN: **7393487048935**

Crimp geometries: **Punch, Dual, Hexagonal, Oval**
Working pressure (MPa): **63**

AWG/MCM Stranded Al: **6 AWG - 1250 MCM**
AWG/MCM Solid Al: **6 AWG - 550 MCM**
AWG/MCM Cu: **8 AWG - 1600 MCM**
mm² Stranded Al: **16-630**
mm² Solid Al: **16-300**
mm² Cu: **10-800**
Crimp range Cu-terminals min (mm²): **10**
Crimp range Cu-terminals max (mm²): **800**
Crimp range C-connectors min (mm²): **6**
Crimp range C-connectors max (mm²): **300**
Crimp range Al-terminals min (mm²): **16**
Crimp range Al-terminals max (mm²): **630**

Matching items

Product	mm ² KR/KS, KRF/KSF	mm ² KRT/KST	mm ² KRD/KSD
DB2522	120	150	150
DB2525	150	—	185
DB2527	185	—	240



ELPRESS

Product	mm ² KR/KS, KRF/KSF	mm ² KRT/KST	mm ² KRD/KSD
DB2530	240	300	300
DB2532	300	400	400
DB2538	400	—	—