

250-system (25 t)

V250

- ✓ fitted with safety device in the form of a protective cover
- ✓ working pressure 63 MPa (630 bar)
- ✓ crimp force 250 kN (25 tonnes)
- ✓ light and versatile steel crimp head

Crimp head for contact crimping Cu terminals, type KRF/KSF 10-800 mm², Al terminals 16-630 mm² (-300 solid), C sleeves 6/6-300/300 mm². Used in conjunction with Elpress foot pump P4000 or battery and mains powered pump PS710.



Item number: **5208-250000**

EAN: **7393487035911**

Crimp geometries: **Punch, Hexagonal, Oval**

Safety device: **Protective cover**

Working pressure (MPa): **63**

Quick connector: **Yes**

AWG/MCM Stranded Al: **6 AWG - 1250 MCM**

AWG/MCM Solid Al: **6 AWG - 550 MCM**

AWG/MCM Cu: **8 AWG - 1600 MCM**

mm² Stranded Al: **16-630**

mm² Solid Al: **16-300**

mm² Cu: **10-800**

Crimp range Cu-terminals min (mm²): **10**

Crimp range Cu-terminals max (mm²): **800**

Crimp range C-connectors min (mm²): **6**

Crimp range C-connectors max (mm²): **300**

Crimp range Al-terminals min (mm²): **16**

Crimp range Al-terminals max (mm²): **630**



Matching items

Product	mm ² KR/KS, KRF/KSF	mm ² KRT/KST	mm ² KRD/KSD
B6DIN	—	—	—
B6FE	—	—	—
B7	—	10	—
B8	10	—	16

ELPRESS

Product	mm ² KR/KS, KRF/KSF	mm ² KRT/KST	mm ² KRД/KSD
B8,5	—	16	—
B8DIN	—	—	—
B8FE	—	—	—
B9	16	—	25
B10	—	25	—
B10DIN	—	—	—
B11	25	—	35
B12	—	35	50
B12DIN	—	—	—
B13	35	—	—
B14	—	50	70
B14,5	50	—	—
B14DIN	—	—	—
B16	—	70	95
B16DIN	—	—	—
B16NP	—	—	—
B17	70	—	—
B18	—	95	—
B18DIN	—	—	—
B19	—	120	120
B20	95	—	—
B20DIN	—	—	—
B20NP	—	—	—
B22	120	150	150
B22DIN	—	—	—
B24	—	185	—
B25	150	—	185
B25C15	—	—	—

Product	mm ² KR/KS, KRF/KSF	mm ² KRT/KST	mm ² KRD/KSD
B25C18	—	—	—
B25C21	—	—	—
B25DIN	—	—	—
B26	—	240	—
B26NP	—	—	—
B27	185	—	240
B28DIN	—	—	—
B30	240	300	300
B32	300	400	400
B2525L	150	—	—
B2532	300	400	400
B2538	400	—	—
B2540	—	500	500
B2542	500	—	—
B2545	—	630	630
B2553	630	800	800
BC5	—	—	—
BC6	—	—	—
BC8-9	—	—	—
BC13	—	—	—
BC15	—	—	—