

Shearbolt connectors 10 - 240 mm<sup>2</sup> (pre-assembled screw)

# SC150N

- ✓ shearbolt material: brass, for minimum friction
- ✓ pre-threaded shear-off shearbolts for easy handling
- ✓ with partition wall
- ✓ voltage range: 1 kV
- ✓ meets the requirements of IEC standard 61238-1:2003

Shearbolt connector 1 kV that is suitable for both Al and Cu class 1 and class 2 cable. Round cable 70-150 mm<sup>2</sup>, sector shaped cable 70-150 mm<sup>2</sup>. When splicing screen conductors 21-95 mm<sup>2</sup>, filler piece SC150N/PEN is used for splicing the copper screen of the cable.



Item number: **7320-011400**

EAN: **7393487049291**

d (mm): **19.5**

D (mm): **23,0**

L (mm): **80**

s (mm) - strip length: **39**

Max voltage (kV): **1**

Screen conductor (mm<sup>2</sup>): **120-146**

Screen conductor (with filling piece), Min (mm<sup>2</sup>): **21-95 (SC150N/PEN)**

Screen conductor (with filling piece), Max (mm<sup>2</sup>): **21-95 (SC150N/PEN)**

Cable type Round (mm<sup>2</sup>): **70-150**

Cable type Sector (mm<sup>2</sup>): **70-150**

