

1300-järjestelmä (H)

PVX1300-US

- ✓ ergonomic design
- ✓ swivel fork
- ✓ crimp force control using pressure monitoring
- ✓ DUAL crimp technology
- ✓ fast-forward feed
- ✓ display with information about the tool and service intervals
- ✓ crimp monitoring with warning lamp (LED)
- ✓ 2 year warranty
- ✓ Delivered with battery and US-charger



Battery-powered crimp gun for contact crimping Cu terminals, type KRF/KSF 10-400 mm², Al terminals 16-400 mm² (-240 solid), C sleeves 6/6-120/120 mm².



Tuotenumero: **5204-011000**

EAN: **7393487061194**

Toimituslaatikko: **Muovikotelo**

Käyttölämpötila, min. (°C): **-20**

Käyttölämpötila, maks. (°C): **40**

Puristusgeometria: **Punch, Dual, Hexagonal, Oval**

Paineen valvonta näytön kautta: **kyllä**

Latausaika (min.): **15**

Akku: **Li-Ion Makita, 5,0Ah, 18V**

Akkujen määrä: **1**

AWG/MCM Säikeinen Al: **7 AWG - 700 MCM**

AWG/MCM Kiinteä Al: **7 AWG - 450 MCM**

AWG/MCM Cu: **8 AWG - 700 MCM**

mm² Säikeinen Al: **16-400**

mm² Kiinteä Al: **16-240**

mm² Cu: **10-400**

mm² KR/KS, KRF/KSF: **10-400**

mm² KRT/KST: **10-400**

mm² KRD/KSD: **10-400**

Puristusalue Cu-päätteet min. (mm²): **10**

Puristusalue Cu-päätteet maks. (mm²): **400**

Puristusalue C-liittimet min. (mm²): **6**

Puristusalue C-liittimet maks. (mm²): **120**

Puristusalue Al-päätteet min. (mm²): **16**

Puristusalue Al-päätteet maks. (mm²): **400**

ELPRESS

Matching items

Product	mm ² KR/KS, KRF/KSF	mm ² KRT/KST	mm ² KRD/KSD
13B11	25	—	35
13B22	120	150	150
13B25	150	—	185
13B25DIN	—	—	—
13B26	—	240	—
13B27	185	—	240
13B28DIN	—	—	—
13B30	240	300	300
13B32	300	400	400
13B38	400	—	—
13BC13	—	—	—
13BC15	—	—	—
13DB8	10	—	—
13DB9	16	—	—
13DB11	25	—	—
13DB13	35	—	—
13DB14,5	50	—	—
13DB17	70	—	—
13DB20	95	—	—
13DB22	120	—	—
13DB25	150	—	—
13DB27	185	—	—
13DB30	240	—	—
13DB32	300	—	—
13P13M2	—	—	—
B6DIN	—	—	—
B6FE	—	—	—

Product	mm² KR/KS, KRF/KSF	mm² KRT/KST	mm² KR D/KSD
B7	—	10	—
B8	10	—	16
B8,5	—	16	—
B8DIN	—	—	—
B8FE	—	—	—
B9	16	—	25
B10	—	25	—
B10DIN	—	—	—
B11	25	—	35
B12	—	35	50
B12DIN	—	—	—
B13	35	—	—
B14	—	50	70
B14,5	50	—	—
B14DIN	—	—	—
B16	—	70	95
B16DIN	—	—	—
B16NP	—	—	—
B17	70	—	—
B18	—	95	—
B18DIN	—	—	—
B19	—	120	120
B20	95	—	—
B20DIN	—	—	—
B20NP	—	—	—
B22	120	150	150
B22DIN	—	—	—
B24	—	185	—

Product	mm² KR/KS, KRF/KSF	mm² KRT/KST	mm² KRD/KSD
B25	150	—	185
BC5	—	—	—
BC6	—	—	—
BC8-9	—	—	—