

600-järjestelmä (6 t)

PVX611-US

- ✓ same crimp dies as V611 and V600
- ✓ ergonomic design ensures optimum balance in the user's hand
- ✓ swivel opening crimp fork
- ✓ fast-forward feeding for more efficient crimping
- ✓ display with information about the tool and service intervals

Tested and certified battery-powered crimping tool for contact crimping Cu-terminals, type KRF/KSF 10-150 mm², Al-terminals 16-25 mm² (-35 solid), C sleeves 6/6-50/50 mm².



Tuotenumero: **5204-012000**

EAN: **7393487061286**

Pikakelaus eteenpäin -toiminto: **kyllä**

Toimituslaatikko: **Muovikotelo**

Käyttölämpötila, min. (°C): **-20**

Käyttölämpötila, maks. (°C): **40**

Puristusgeometria: **Punch, Hexagonal, Oval**

Suojalaite: **Closedchassis**

Paineen valvonta näytön kautta: **kyllä**

Työvalo: **kyllä**

Laturi: **Li-Ion Makita**

Latausaika (min.): **15**

Akkujen määrä: **1**

Puristusaika (s): **3-6, depending on size**

Puristimet/lataus: **100-200 depending on size and temperature**

AWG/MCM Säikeinen Al: **7 - 4 AWG**

AWG/MCM Kiinteä Al: **7 - 2 AWG**

AWG/MCM Cu: **18 - 10 AWG**

mm² Säikeinen Al: **16-25**

mm² Kiinteä Al: **16-35**

mm² Cu: **10-240**

mm² KR/KS, KRF/KSF: **10-150**

mm² KRT/KST: **10-240**

mm² KRD/KSD: **16-185**

Puristusalue Cu-päätteet min. (mm²): **10**

Puristusalue Cu-päätteet maks. (mm²): **240**

Puristusalue C-liittimet min. (mm²): **6**

Puristusalue C-liittimet maks. (mm²): **50**

Puristusalue Al-päätteet min. (mm²): **16**

Puristusalue Al-päätteet maks. (mm²): **25**



Matching items

Product	mm ² KR/KS, KRF/KSF	ItemMM2KRTdKST	ItemMM2KRdKSD
KB22L	120	—	—
KB70ET	—	—	—
KB95ET	—	—	—
KB120ET	—	—	—
TB11L	25	—	—
TB13L	35	—	—
TB14,5L	50	—	—
TB17L	70	—	—
TB20L	95	—	—