

Elpress mini

- electro-hydraulic crimping tool 6 to 70 mm²



The Elpress mini tool PVL350 in a new sleek design with a high performance Li-Ion battery that streamlines your work with its improved battery capacity.

CHARACTERISTICS:

- Single-handed operation for easy control of all tool functions
- Slim fitting crimping head – ideal for confined spaces
- High-performance 12 V Li-Ion battery – with indication of charge status
- Opening, rotatable “flip-top” head for easy die change and good accessibility
- Easy and comfortable to use with one hand thanks to its ergonomic 2-component housing with grip-friendly protection
- Extremely lightweight and rapid crimping process for maximum efficiency
- Automatic return of dies when crimping is completed

TECHNICAL DATA PVL350:

Crimping force	35 kN
Crimping range	6-70 mm ²
Crimping process	about 3-4 s (dependent on material)
Battery voltage	12 V
Battery capacity	2 Ah, Li-Ion
Charge time	about 90 minutes.
Weight including battery	1.6 kg
Ambient temperature	-10°C to +40°C
Dimensions	330 x 85 x 60 mm

Elpress MINI – crimping dies



Application	Area	Dies	
CUT-connector	6-16 mm ²	MB4016	
	KR/KRD, KS/KSD	KR/KRF, KS/KSF	KRT/KST
Hexagonal 4-10 mm ²	MB4016	MB4016	-
Hexagonal 10 mm ²	MB8	MB8	MB7
16 mm ²	MB8	MB9	MB8,5
25 mm ²	MB9	MB11	MB10
35 mm ²	MB11	MB13	MB12
50 mm ²	MB12	MB14,5	MB14
70 mm ²	MB14	MB17	MB16
95 mm ²	MB17		
C-connectors	12-26 mm ² (C6-10) 30-50 mm ² (C16-25)	MBC5 MBC6	

