

1300-system (C2)

PVX1300C2

- ✓ open C-format crimp head
- ✓ DUAL crimp technology
- ✓ ergonomic design
- ✓ swivel fork
- ✓ crimp force control using pressure monitoring
- ✓ display with information about the tool and service intervals
- ✓ crimp monitoring with warning lamp (LED)



Battery powered crimp gun for contact crimping
Cu-terminals, type KRF/KSF 10-300 mm², C-sleeves
6/6-120/120 mm².



Item number: **5204-011300**

EAN: **7393487061224**

Ratchet function that does not trigger until
completed crimp: **Yes**

Delivery box: **Plastic case**

Working temperature, Min (°C): **-20**

Working temperature, Max (°C): **40**

Crimp geometries: **Dual, Hexagonal, Oval**

Pressure monitoring via display: **Yes**

Work light: **Yes**

Charger: **Li-ion & Ni-MH 7.2-18V**

Charge time (min): **15**

Battery: **Li-Ion Makita, 5,0Ah, 18V**

No. of batteries: **1**

Crimp time (s): **4-12, depending on size**

Crimps/charge: **60-120 depending on size and temperature**

AWG/MCM Cu: **8 AWG - 700 MCM**

mm² Cu: **10-400**

Crimp range Cu-terminals min (mm²): **10**

Crimp range Cu-terminals max (mm²): **400**

Crimp range C-connectors min (mm²): **6**

Crimp range C-connectors max (mm²): **120**

Matching items

Product	mm ² KR/KS, KRF/KSF	mm ² KRT/KST	mm ² KRD/KSD
13B11L	25	—	—

ELPRESS

Product	mm ² KR/KS, KRF/KSF	mm ² KRT/KST	mm ² KRD/KSD
13B12	—	35	50
13B14	—	50	70
13B16	—	70	95
13B19	—	120	120
13C21B38	400	—	—
13CB13	35	—	—
13CB22	120	150	150
13CBC13	—	—	—
13CBC15	—	—	—
13DCB8	10	—	—
13DCB9	16	—	—
13DCB11	25	—	—
13DCB13	35	—	—
13DCB14,5	50	—	—
13DCB17	70	—	—
13DCB20	95	—	—
13DCB22	120	—	—
13DCB25	150	—	—
13DCB27	185	—	—
13DCB30	240	—	—
13DCB32	300	—	—
BC5	—	—	—
BC6	—	—	—
BC8-9	—	—	—