

1300-system (C2)

V1311C2-A

- ✓ open C-format crimp head
- ✓ fast-forward feed system
- ✓ integrated ratchet system that does not release until the crimp is complete
- ✓ fork can swivel 180°
- ✓ crimp force 130 kN
- ✓ ergonomic handle
- ✓ easy to carry and work with
- ✓ requires low handle force, approx 245 N at max force

Tested and certified hydraulic hand tool for contact crimping Cu terminals, type KRF/KSF 10-300 mm², C-sleeves 6/6-120/120 mm².



Item number: **5202-131400**

EAN: **7393487059733**

Fast forward function: **Yes**

Ratchet function that does not trigger until completed crimp: **Yes**

Delivery box: **Plywood box**

Working temperature, Min (°C): **-22**

Working temperature, Max (°C): **55**

Crimp geometries: **Hexagonal, Oval**

AWG/MCM Cu: **8 AWG - 700 MCM**

mm² Cu: **10-400**

Crimp range Cu-terminals min (mm²): **10**

Crimp range Cu-terminals max (mm²): **400**

Crimp range C-connectors min (mm²): **6**

Crimp range C-connectors max (mm²): **120**



Matching items

Product	mm ² KR/KS, KRF/KSF	mm ² KRT/KST	mm ² KRD/KSD
---------	--------------------------------	-------------------------	-------------------------

EIPRESS

13B11L	25	—	—
13B12	—	35	50
13B14	—	50	70
13B16	—	70	95
13B19	—	120	120
13BC8-9	—	—	—
13C21B38	400	—	—
BC5	—	—	—
BC6	—	—	—
BC8-9	—	—	—