

1300-system (H)

# PVX1300- WOBC

- ✓ ergonomic design
- ✓ swivel fork
- ✓ crimp force control using pressure monitoring
- ✓ DUAL crimp technology
- ✓ fast-forward feed
- ✓ display with information about the tool and service intervals
- ✓ crimp monitoring with warning lamp (LED)
- ✓ 2 year warranty
- ✓ Delivered without Battery/Charger

Battery-powered crimp gun for contact crimping Cu terminals, type KRF/KSF 10-400 mm<sup>2</sup>, Al terminals 16-400 mm<sup>2</sup> (-240 solid), C sleeves 6/6-120/120 mm<sup>2</sup>.



Item number: **5204-012200**  
EAN: **7393487061804**

Delivery box: **Plastic case**  
Working temperature, Min (°C): **-20**  
Working temperature, Max (°C): **40**  
Crimp geometries: **Punch, Dual, Hexagonal, Oval**  
Pressure monitoring via display: **Yes**  
Charge time (min): **15**

AWG/MCM Stranded Al: **6 AWG - 700 MCM**  
AWG/MCM Solid Al: **6 AWG - 450 MCM**  
AWG/MCM Cu: **8 AWG - 700 MCM**  
mm<sup>2</sup> Stranded Al: **16-400**  
mm<sup>2</sup> Solid Al: **16-240**  
mm<sup>2</sup> Cu: **10-400**  
mm<sup>2</sup> KR/KS, KRF/KSF: **10-400**  
mm<sup>2</sup> KRT/KST: **10-400**  
mm<sup>2</sup> KRD/KSD: **10-400**  
Crimp range Cu-terminals min (mm<sup>2</sup>): **10**  
Crimp range Cu-terminals max (mm<sup>2</sup>): **400**  
Crimp range C-connectors min (mm<sup>2</sup>): **6**  
Crimp range C-connectors max (mm<sup>2</sup>): **120**  
Crimp range Al-terminals min (mm<sup>2</sup>): **16**

Crimp range Al-terminals max (mm<sup>2</sup>): 400



## Matching items

Product	mm <sup>2</sup> KR/KS, KRF/KSF	mm <sup>2</sup> KRT/KST	mm <sup>2</sup> KRD/KSD
13B11	25	—	35
13B22	120	150	150
13B25	150	—	185
13B25DIN	—	—	—
13B26	—	240	—
13B27	185	—	240
13B28DIN	—	—	—
13B30	240	300	300
13B32	300	400	400
13B38	400	—	—
13BC13	—	—	—
13BC15	—	—	—
13DB8	10	—	—
13DB9	16	—	—
13DB11	25	—	—
13DB13	35	—	—
13DB14,5	50	—	—
13DB17	70	—	—

<b>Product</b>	<b>mm<sup>2</sup> KR/KS, KRF/KSF</b>	<b>mm<sup>2</sup> KRT/KST</b>	<b>mm<sup>2</sup> KRD/KSD</b>
13DB20	95	—	—
13DB22	120	—	—
13DB25	150	—	—
13DB27	185	—	—
13DB30	240	—	—
13DB32	300	—	—
B6DIN	—	—	—
B6FE	—	—	—
B7	—	10	—
B8	10	—	16
B8,5	—	16	—
B8DIN	—	—	—
B8FE	—	—	—
B9	16	—	25
B10	—	25	—
B10DIN	—	—	—
B11	25	—	35
B12	—	35	50
B12DIN	—	—	—
B13	35	—	—
B14	—	50	70
B14,5	50	—	—
B14DIN	—	—	—
B16	—	70	95
B16DIN	—	—	—
B16NP	—	—	—
B17	70	—	—
B18	—	95	—

<b>Product</b>	<b>mm<sup>2</sup> KR/KS, KRF/KSF</b>	<b>mm<sup>2</sup> KRT/KST</b>	<b>mm<sup>2</sup> KRD/KSD</b>
B18DIN	—	—	—
B19	—	120	120
B20	95	—	—
B20DIN	—	—	—
B20NP	—	—	—
B22	120	150	150
B22DIN	—	—	—
B24	—	185	—
B25	150	—	185
BC5	—	—	—
BC6	—	—	—
BC8-9	—	—	—