

250-system (25 t)

# DV250

- ✓ crimp head with patented DUAL technology that gives optimised hexagonal crimping + a certain amount of indented crimping in two integrated steps
- ✓ fitted with safety device in the form of a protective cover
- ✓ working pressure 63 MPa (630 bar)
- ✓ crimp force 250 kN (25 tonnes)
- ✓ light and versatile steel crimp head

Crimp head for contact crimping Cu terminals, type KRF/KSF 120-400 mm<sup>2</sup>. Used in conjunction with Elpress foot pump P4000 or battery and mains powered pump PS710.



Item number: **5208-250200**

EAN: **7393487048935**

Crimp geometries: **Punch, Dual, Hexagonal, Oval**  
Working pressure (MPa): **63**

AWG/MCM Stranded Al: **6 AWG - 1250 MCM**

AWG/MCM Solid Al: **6 AWG - 550 MCM**

AWG/MCM Cu: **8 AWG - 1600 MCM**

mm<sup>2</sup> Stranded Al: **16-630**

mm<sup>2</sup> Solid Al: **16-300**

mm<sup>2</sup> Cu: **10-800**

Crimp range Cu-terminals min (mm<sup>2</sup>): **10**

Crimp range Cu-terminals max (mm<sup>2</sup>): **800**

Crimp range C-connectors min (mm<sup>2</sup>): **6**

Crimp range C-connectors max (mm<sup>2</sup>): **300**

Crimp range Al-terminals min (mm<sup>2</sup>): **16**

Crimp range Al-terminals max (mm<sup>2</sup>): **630**

## Matching items

Product	mm <sup>2</sup> KR/KS, KRF/KSF	mm <sup>2</sup> KRT/KST	mm <sup>2</sup> KR/D/KSD
DB2522	120	150	150
DB2525	150	—	185
DB2527	185	—	240



**ELPRESS**

<b>Product</b>	<b>mm<sup>2</sup> KR/KS, KRF/KSF</b>	<b>mm<sup>2</sup> KRT/KST</b>	<b>mm<sup>2</sup> KRD/KSD</b>
DB2530	240	300	300
DB2532	300	400	400
DB2538	400	—	—