

V1470

- ✓ fitted with safety device in the form of a protective cover and with quick coupler
- ✓ working pressure 63 MPa (630 bar)
- ✓ crimp force 400 kN
- ✓ supplied in plywood box



Tested and certified crimp head for crimping Cu-terminals 500-1000 mm², Al-terminals 800-1200 mm², C-sleeves 245-600 mm². Used in conjunction with Elpress foot pump P4000 or battery and mains powered pump PS710.



Item number: **5208-404000**

EAN: **7393487000568**

Delivery box: **Plywood box**

Crimp geometries: **Punch, Hexagonal, Oval**

Safety device: **Protective cover**

Working pressure (MPa): **63**

Quick connector: **Yes**

AWG/MCM Stranded Al: **1600 - 2500 MCM**

AWG/MCM Cu: **1000 - 2000 MCM**

mm² Stranded Al: **800-1200**

mm² Cu: **500-1000**

Crimp range Cu-terminals min (mm²): **500**

Crimp range Cu-terminals max (mm²): **1000**

Crimp range C-connectors min (mm²): **150**

Crimp range C-connectors max (mm²): **300**

Crimp range Al-terminals min (mm²): **800**

Crimp range Al-terminals max (mm²): **1200**

Matching items

Product	mm ² KR/KS, KRF/KSF	mm ² KRT/KST	mm ² KRD/KSD
B40C18	—	—	—
B40C21	—	—	—
B4040	—	500	500
B4042	500	—	—
B4045	—	630	630

Product	mm² KR/KS, KRF/KSF	mm² KRT/KST	mm² KRD/KSD
B4053	630 / 800	800	800
B4056	—	1000	1000