

600-system (6 t)

V600

- ✓ same crimp dies as V611 and PVX611
- ✓ crimp force 55 kN
- ✓ delivered in sturdy fabric bag with room for 10 dies

Crimp head for contact crimping of Cu terminals, type, KRF/KSF 10-150 mm², Al terminals 16-25 mm² (-35 solid), C-sleeves 6/6-50/50 mm². Used in conjunction with Elpress foot pump P4000 or battery and mains powered pump PS710.



Item number: **5208-060000**
EAN: **7393487037342**

Delivery box: **Textile bag**
Crimp geometries: **Punch, Hexagonal, Oval**
Working pressure (MPa): **63**

AWG/MCM Stranded Al: **6 - 4 AWG**

AWG/MCM Solid Al: **6 - 2 AWG**

AWG/MCM Cu: **18 - 10 AWG**

mm² Stranded Al: **16-25**

mm² Solid Al: **16-35**

mm² Cu: **10-240**

mm² KR/KS, KRF/KSF: **10-150**

mm² KRT/KST: **10-240**

mm² KRD/KSD: **16-185**

Crimp range C-connectors min (mm²): **6/6**

Crimp range C-connectors max (mm²): **50/50**

Crimp range Al-terminals min (mm²): **16**

Crimp range Al-terminals max (mm²): **25**



82

0548

TB 14.5

03

14.5

0548



V600

EIPRESS

Matching items

Product	mm ² KR/KS, KRF/KSF	mm ² KRT/KST	mm ² KR D/KSD
KB22	120	150	150
KB22L	120	—	—
KB24	—	185	—
KB25	150	—	185
KB26	—	240	—
KB70ET	—	—	—
KB95ET	—	—	—
KB120ET	—	—	—
TB6-8DIN	—	—	—
TB7-19	—	10 / 120	120
TB7-20	10 / 95	10	—
TB8,5-18	—	16 / 95	—
TB8-14	10	50	16 / 70
TB8-17	10 / 70	—	16
TB8-18	10	10 / 95	—
TB9-12	—	35	25 / 50
TB9-13	16 / 35	—	25
TB9-20	16 / 95	—	—
TB10-12DIN	—	—	—
TB10-16	—	25 / 70	95
TB11-14,5	25 / 50	—	—
TB11-16	25	70	35 / 95
TB11L	25	—	—
TB12-14	—	35 / 50	50 / 70
TB13L	35	—	—
TB14,5-17	—	—	—

Product	mm² KR/KS, KRF/KSF	mm² KRT/KST	mm² KRD/KSD
TB14,5L	50	—	—
TB14-16DIN	—	—	—
TB17L	70	—	—
TB18DIN	—	—	—
TB20L	95	—	—
TBC5-C6	—	—	—
TBC89-B13	35	—	—
TBKA9-11,5	10-16	—	—
TBNP16-20	—	—	—