

Through connectors of aluminium 16 - 95 mm<sup>2</sup> to  
solid copper 10 mm<sup>2</sup>

# AKS25-10S

- ✓ Transition joints from stranded Al conductors to solid Cu conductors 10 mm<sup>2</sup> (e.g. Excel, Excelett).
- ✓ Two crimps are needed for both Al and Cu.

AlCu through connector, from Al conductor to Cu conductor for stranded Al cable 25 mm<sup>2</sup>, or for solid Al-cable 35 mm<sup>2</sup>, to solid Cu cable 10 mm<sup>2</sup>. When hexagonal crimping Cu conductors, the dies are placed in the middle between the marking groove and the outer edge. Used with Elpress certified systems V1300, V250.



Item number: **7333-407100**

EAN: **7393487020641**

s1 (mm): **33**

d (mm): **6.8**

D (mm): **13**

L (mm): **64.5**

d1 (mm): **4.5**

D1 (mm): **7**

s (mm) - strip length: **29**

AWG/MCM Stranded Al: **4 AWG**

AWG/MCM Solid Al: **2 AWG**

AWG/MCM Cu: **8 AWG**

mm<sup>2</sup> Stranded Al: **25**

mm<sup>2</sup> Solid Al: **35**

mm<sup>2</sup> Cu: **10**

