

1300-system (C2)

DV1300C2

- ✓ Open C-format crimp head with patented DUAL technology that provides optimised hexagonal crimping + a certain amount of indented crimping in two integrated steps
- ✓ working pressure 63 MPa (630 bar)
- ✓ crimp force 130 kN

Crimp head for contact crimping Cu terminals, type KRF/KSF 10-300 mm². Used in conjunction with Elpress foot pump P4000 or battery and mains powered pump PS710.



Item number: **5208-134400**
EAN: **7393487059726**

Ratchet function that does not trigger until completed crimp: **Yes**
Working temperature, Min (°C): **-20**
Working temperature, Max (°C): **40**
Crimp geometries: **Dual, Hexagonal, Oval**
Quick connector: **Yes**

AWG/MCM Cu: **8 AWG - 700 MCM**
mm² Cu: **10-400**
Crimp range Cu-terminals min (mm²): **10**
Crimp range Cu-terminals max (mm²): **400**
Crimp range C-connectors min (mm²): **25**
Crimp range C-connectors max (mm²): **240**



Matching items

Product	mm ² KR/KS, KRF/KSF	mm ² KRT/KST	mm ² KR/D/KSD
13B11L	25	—	—
13B12	—	35	50
13B14	—	50	70
13B16	—	70	95

ELPRESS

Product	mm² KR/KS, KRF/KSF	mm² KRT/KST	mm² KRD/KSD
13B19	—	120	120
13BC8-9	—	—	—
13CB13	35	—	—
13CB22	120	150	150
13CBC13	—	—	—
13CBC15	—	—	—
13DCB8	10	—	—
13DCB8-6	—	—	—
13DCB9	16	—	—
13DCB11	25	—	—
13DCB13	35	—	—
13DCB14,5	50	—	—
13DCB17	70	—	—
13DCB20	95	—	—
13DCB22	120	—	—
13DCB25	150	—	—
13DCB27	185	—	—
13DCB30	240	—	—
13DCB32	300	—	—