

1300-system (H)

V1300

- ✓ working pressure 63 MPa (630 bar)
- ✓ crimp force 130 kN (13 tonnes)
- ✓ light and versatile steel crimp head

Crimp head for contact crimping Cu terminals, type KRF/KSF 10-400 mm², Al terminals 16-400 mm² (-240 solid), C sleeves 6/6-120/120 mm². Used in conjunction with foot pump P4000 or battery and mains powered pump PS710.



Item number: **5208-132500**

EAN: **7393487000520**

Crimp geometries: **Punch, Hexagonal, Oval**

Safety device: **Protective cover**

Working pressure (MPa): **63**

Quick connector: **Yes**

AWG/MCM Stranded Al: **6 AWG - 700 MCM**

AWG/MCM Solid Al: **6 AWG - 450 MCM**

AWG/MCM Cu: **8 AWG - 700 MCM**

mm² Stranded Al: **16-400**

mm² Solid Al: **16-240**

mm² Cu: **10-400**

Crimp range Cu-terminals min (mm²): **10**

Crimp range Cu-terminals max (mm²): **400**

Crimp range C-connectors min (mm²): **6**

Crimp range C-connectors max (mm²): **120**

Crimp range Al-terminals min (mm²): **16**

Crimp range Al-terminals max (mm²): **400**



Matching items

| Product | mm ² KR/KS, KRF/KSF | mm ² KRT/KST | mm ² KRD/KSD |
|---------|--------------------------------|-------------------------|-------------------------|
| 13B11L | 25 | — | — |

ELPRESS

| Product | mm² KR/KS, KRF/KSF | mm² KRT/KST | mm² KRD/KSD |
|----------------|--------------------------------------|-------------------------------|-------------------------------|
| 13B12 | — | 35 | 50 |
| 13B13 | 35 | — | — |
| 13B14 | — | 50 | 70 |
| 13B14,5LS | — | — | — |
| 13B16 | — | 70 | 95 |
| 13B19 | — | 120 | 120 |
| 13B20 | 95 | — | — |
| 13B22 | 120 | 150 | 150 |
| 13B25 | 150 | — | 185 |
| 13B25DIN | — | — | — |
| 13B26 | — | 240 | — |
| 13B27 | 185 | — | 240 |
| 13B28DIN | — | — | — |
| 13B30 | 240 | 300 | 300 |
| 13B32 | 300 | 400 | 400 |
| 13B38 | 400 | — | — |
| 13BC8-9 | — | — | — |
| 13BC13 | — | — | — |
| 13BC15 | — | — | — |
| 13P13M2 | — | — | — |
| B6DIN | — | — | — |
| B6FE | — | — | — |
| B7 | — | 10 | — |
| B8 | 10 | — | 16 |
| B8,5 | — | 16 | — |
| B8DIN | — | — | — |
| B8FE | — | — | — |
| B9 | 16 | — | 25 |

| Product | mm² KR/KS, KRF/KSF | mm² KRT/KST | mm² KRD/KSD |
|----------------|--------------------------------------|-------------------------------|-------------------------------|
| B10 | — | 25 | — |
| B10DIN | — | — | — |
| B11 | 25 | — | 35 |
| B12 | — | 35 | 50 |
| B12DIN | — | — | — |
| B13 | 35 | — | — |
| B14 | — | 50 | 70 |
| B14,5 | 50 | — | — |
| B14DIN | — | — | — |
| B16 | — | 70 | 95 |
| B16DIN | — | — | — |
| B16NP | — | — | — |
| B17 | 70 | — | — |
| B18 | — | 95 | — |
| B18DIN | — | — | — |
| B19 | — | 120 | 120 |
| B20 | 95 | — | — |
| B20DIN | — | — | — |
| B20NP | — | — | — |
| B22 | 120 | 150 | 150 |
| B22DIN | — | — | — |
| B24 | — | 185 | — |
| B25 | 150 | — | 185 |
| BC5 | — | — | — |
| BC6 | — | — | — |
| BC8-9 | — | — | — |