

V1470-system (40 t)

V1470

- ✓ fitted with safety device in the form of a protective cover and with quick coupler
- ✓ working pressure 63 MPa (630 bar)
- ✓ crimp force 400 kN
- ✓ supplied in plywood box



Tested and certified crimp head for crimping Cu-terminals 500-1000 mm², Al-terminals 800-1200 mm², C-sleeves 245-600 mm². Used in conjunction with Elpress foot pump P4000 or battery and mains powered pump PS710.



Item number: **5208-404000**

EAN: **7393487000568**

Delivery box: **Plywood box**

Crimp geometries: **Punch, Hexagonal, Oval**

Safety device: **Protective cover**

Working pressure (MPa): **63**

Quick connector: **Yes**

AWG/MCM Stranded Al: **1600 - 2500 MCM**

AWG/MCM Cu: **1000 - 2000 MCM**

mm² Stranded Al: **800-1200**

mm² Cu: **500-1000**

Crimp range Cu-terminals min (mm²): **500**

Crimp range Cu-terminals max (mm²): **1000**

Crimp range C-connectors min (mm²): **150**

Crimp range C-connectors max (mm²): **300**

Crimp range Al-terminals min (mm²): **800**

Crimp range Al-terminals max (mm²): **1200**

Matching items

| Product | mm ² KR/KS, KRF/KSF | mm ² KRT/KST | mm ² KRD/KSD |
|---------|--------------------------------|-------------------------|-------------------------|
| B40C18 | — | — | — |
| B40C21 | — | — | — |
| B4040 | — | 500 | 500 |
| B4042 | 500 | — | — |
| B4045 | — | 630 | 630 |

ELPRESS

| Product | mm² KR/KS, KRF/KSF | mm² KRT/KST | mm² KRD/KSD |
|----------------|--------------------------------------|-------------------------------|-------------------------------|
| B4053 | 630 / 800 | 800 | 800 |
| B4056 | — | 1000 | 1000 |