

600-system (6 t)

# PVX611-US

- ✓ same crimp dies as V611 and V600
- ✓ ergonomic design ensures optimum balance in the user's hand
- ✓ swivel opening crimp fork
- ✓ fast-forward feeding for more efficient crimping
- ✓ display with information about the tool and service intervals

Tested and certified battery-powered crimping tool for contact crimping Cu-terminals, type KRF/KSF 10-150 mm<sup>2</sup>, Al-terminals 16-25 mm<sup>2</sup> (-35 solid), C sleeves 6/6-50/50 mm<sup>2</sup>.



Item number: **5204-012000**

EAN: **7393487061286**

Fast forward function: **Yes**

Delivery box: **Plastic case**

Working temperature, Min (°C): **-20**

Working temperature, Max (°C): **40**

Crimp geometries: **Punch, Hexagonal, Oval**

Safety device: **Closed chassis**

Pressure monitoring via display: **Yes**

Work light: **Yes**

Charger: **Li-Ion Makita**

Charge time (min): **15**

No. of batteries: **1**

Crimp time (s): **3-6, depending on size**

Crimps/charge: **100-200 depending on size and temperature**

AWG/MCM Stranded Al: **6 - 4 AWG**

AWG/MCM Solid Al: **6 - 2 AWG**

AWG/MCM Cu: **18 - 10 AWG**

mm<sup>2</sup> Stranded Al: **16-25**

mm<sup>2</sup> Solid Al: **16-35**

mm<sup>2</sup> Cu: **10-240**

mm<sup>2</sup> KR/KS, KRF/KSF: **10-150**

mm<sup>2</sup> KRT/KST: **10-240**

mm<sup>2</sup> KRD/KSD: **16-185**

Crimp range Cu-terminals min (mm<sup>2</sup>): **10**

Crimp range Cu-terminals max (mm<sup>2</sup>): **240**

Crimp range C-connectors min (mm<sup>2</sup>): **6**

Crimp range C-connectors max (mm<sup>2</sup>): **50**

Crimp range Al-terminals min (mm<sup>2</sup>): **16**

Crimp range Al-terminals max (mm<sup>2</sup>): **25**





PVX611  
**EIPRESS**  
CE  
ME 1008

## Matching items

| Product | mm <sup>2</sup> KR/KS, KRF/KSF | ItemMM2KRTdKST | ItemMM2KRDdKSD |
|---------|--------------------------------|----------------|----------------|
| KB22L   | 120                            | —              | —              |
| KB70ET  | —                              | —              | —              |
| KB95ET  | —                              | —              | —              |
| KB120ET | —                              | —              | —              |
| TB11L   | 25                             | —              | —              |
| TB13L   | 35                             | —              | —              |
| TB14,5L | 50                             | —              | —              |
| TB17L   | 70                             | —              | —              |
| TB20L   | 95                             | —              | —              |