

C-sleeves 6-300 mm<sup>2</sup>

# C70-95

- ✓ Material: Cu 99.95%, tin plated Cu/Sn.
- ✓ Unique patented solution.
- ✓ Possible to front feed all branches.



**Example of marking: 25-120/140-190** Area min-max /  
Tot. area min-max

**Elpress logotype BC13** Die pair BC13

Branching sleeve for splicing and branching earth lines as well as lightning control installations. Used with Elpress certified systems V1300, V250.



Item number: **7309-300700**

EAN: **7393487062856**

- a (mm): **39**  
b (mm): **30**  
c (mm): **22.2**

mm<sup>2</sup> C-sleeve Cu Range, Min: **140**

mm<sup>2</sup> C-sleeve Cu Range, Max: **190**

Side feed, Cu (mm<sup>2</sup>): **70/70, 95/50-95, 120/25-70**

Front feed, Cu (mm<sup>2</sup>): **70/70, 95/50-70, 120/25-50**

Side feed, Cu (AWG/MCM): **2/0 / 2/0, 3/0 / 1/0-3/0, 4/0/#4-2/0**

Front feed, Cu (AWG/MCM): **2/0 / 2/0, 3/0 / 1/0-2/0, 4/0/#4-1/0**

