

KRF70-12- 90GR

- ✓ Material: Cu 99.95%, tin plated Cu/Sn.
- ✓ Inspection hole.
- ✓ For stranded (class 2) and multi-stranded (class 5) Cu conductors, for multi-stranded Cu conductors contact crimping using the Dual system is recommended.
- ✓ UL-approved, DNV approved.

Example of marking KRF: 17 (neck) Elpress logo 70 10F (palm)

17 = Die No. 70 = mm² 10 = palm hole for M10 F = type KRF for stranded and flexible conductors.
Angled tube terminal 90° for multi-stranded (class 5) and stranded (class 2) Cu conductors (acc. to IEC 60228), 70 mm², with an M12 hole in the palm.
Used with Elpress certified systems V600, V1300, V250.



UK
CA

Item number: **7301-116600**
EAN: **7393487016477**

A (mm): **31.5**
W (mm): **24**
N (mm): **12.5**
N1 (mm): **19.5**
P (mm): **32**
d (mm): **13**
D (mm): **17**
t (mm) - palm thickness: **3.9**
s (mm) - strip length: **22**

Screw: **M12**
Angle (°): **90**
Inspection hole: **Yes**

AWG/MCM Cu: **2/0 AWG**
mm² Cu: **70**

