

KRFS tube terminals 50 - 400 mm<sup>2</sup> with narrow palm

# KRFS240A- 10

- ✓ Material: Cu 99.95%, tin plated Cu/Sn.
- ✓ Inspection hole
- ✓ For stranded (class 2) and multi-stranded (class 5) Cu conductors, for multi-stranded Cu conductors contact crimping using the Dual system is recommended.
- ✓ Easy to install via cable gland, allows for pre-installation.
- ✓ The width of the palm is less than or as wide as the neck.

## Example of marking KRFS: 17 (neck) Elpress logotype 70 10F (palm)

17 = Die no. 70 = mm<sup>2</sup> 10 = palm hole for M10 F = type KRF for stranded and flexible conductors. Tube terminal with narrow palm for multi-stranded (class 5) and stranded (class 2) Cu conductors (acc. to IEC 60228), 240 mm<sup>2</sup>, with an M10 hole in the palm. Used with Elpress certified systems V1300 or V250.



Item number: **7301-292500**

EAN: **7393487062139**

W (mm): **29**  
N (mm): **15**  
N1 (mm): **19**  
P (mm): **34**  
f (mm): **1**  
d (mm): **22.5**  
D (mm): **29**  
L1 (mm): **76**  
L (mm): **91**  
t (mm) - palm thickness: **7.7**  
s (mm) - strip length: **37**

Screw: **M10**

Inspection hole: **Yes**

AWG/MCM Cu: **450 MCM**  
mm<sup>2</sup> Cu: **240**

