

Shearbolt terminals 10 - 630 mm² (pre-assembled screw)

SL240N-10-12

- ✓ shearbolt material: brass for minimum friction
- ✓ threaded shear-off shearbolts for easy handling
- ✓ voltage range 1 kV
- ✓ meets the requirements of IEC standard 61238-1:2003
- ✓ the terminals are of the bimetallic type for best functionality

Shearbolt terminal 1 kV that is suitable for both Al and Cu class 1 and class 2 cable. Round cable 120-240 mm², sector shaped cable 120-240 mm². Suitable for both M10 and M12, reduction washer and flat washer are included when ordering.



Item number: **7334-017000**
EAN: **7393487083554**

W (mm): **31.5**
N (mm): **15**
d (mm): **25**
D (mm): **38/33,1**
L1 (mm): **86**
L (mm): **144.5**
L2 (mm): **31**
t (mm) - palm thickness: **7.6**
s (mm) - strip length: **76**

Screw: **M12, M10**
Max voltage (kV): **1**

Screen conductor (with filling piece), Min (mm²): **29-146 (SC240/PEN)**
Screen conductor (with filling piece), Max (mm²): **29-146 (SC240/PEN)**
Cable type Round (mm²): **120-240**
Cable type Sector (mm²): **120-240**

