

Shearbolt terminals 10 - 630 mm<sup>2</sup> (reversible screw)

# SL150R95S- 10-12

- ✓ shearbolt material: brass for minimum friction
- ✓ reversible shear-off shearbolts
- ✓ voltage range 1-36 kV
- ✓ meets the requirements of IEC standard 61238-1:2003
- ✓ the terminals are of the bimetallic type for best functionality

Shearbolt terminal 1-36 kV that is suitable for both Al and Cu class 1 and class 2 cable. Round cable 95-150 mm<sup>2</sup>, sector shaped cable 95 mm<sup>2</sup>. Suitable for both M10 and M12, reduction washer and flat washer are included when ordering.



Item number: **7334-012100**

EAN: **7393487033801**

a (mm): **12**  
W (mm): **26**  
N (mm): **12.5**  
d (mm): **16**  
D (mm): **27**  
L1 (mm): **75.5**  
L (mm): **116**  
t (mm) - palm thickness: **6.2**  
s (mm) - strip length: **69**

Screw: **M10, M12**

Max voltage (kV): **1-36**

Screen conductor (mm<sup>2</sup>): **70-95**

Cable type Round (mm<sup>2</sup>): **95-150**

Cable type Sector (mm<sup>2</sup>): **95**

